

FRONT SEAT PROTECTORS 2pk

Installation Guide

Safety Information

Before starting, raise your seats to the highest level possible. This will make it easier to attach the seat protector's elasticated hem and straps to fit over the seats.

Do not attach the hooks to any power seat mechanisms, wiring or other parts related to operation of the seat: forward, backward, or up and down.

First determine whether your seats have side airbags: many vehicles come equipped with side airbags mounted within the seat on the sides closest to their respective doors. These airbags deploy during side impact collisions. Many vehicles have a tag or side compartment that indicates the presence of side airbags.

NOTE: this seat cover is not to be used in vehicles equipped with side air bags or on seats that contain air bags. Use of this seat cover may interfere with the deployment of side air bags, which may result in injury to the seated occupant. Always ensure your pet is suitably restrained in the vehicle whilst travelling. Use with a dog harness for ultimate safety. Fits most vehicles.

Seat Protector Care

Wipe the covers clean using a damp cloth or sponge with warm water. Do not put seat covers in a washing machine or tumble dryer. Do not wring, just drip dry. Do not use with heated seats.

Installing the Seat Protectors

Please ensure you carefully check the size of your seats before installing (each cover fits maximum seat **width 66cm** and maximum seat **height 132cm**):



1 Hold the unfolded seat cover by the headrest opening. There's no need to remove or adjust the headrest.



2 Pull the seat cover down over the headrest so that it starts to cover the back of the seat.



3 Continue to pull the seat cover all the way down making sure that any excess fits tightly over the headrest.



4 Start pulling the elasticated bottom part of the seat cover towards you so that it's a tight fit over the seat base.



5 Ensure that the remaining elasticated hem covers all sides of the seat base as taut as possible.



6 Attach the side tether strap over your seat belt buckle. Then attach the hooks to the back tether straps and attach to a secure point at the rear.