

Page 1/10

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2020

Version number 72

Revision: 09.09.2020

Trade name: <u>SIMPLY</u>	® SPRAYS MATT WHITE 500 ML
No further relevant info Sector of Use SU21 Consumer uses. SU22 Professional us Product category PC90 Process category PROC7 Industrial spi PROC11 Non industry	uses of the substance or mixture and uses advised against formation available. Private households / general public / consumers es: Public domain (administration, education, entertainment, services, craftsmen) Coatings and paints, thinners, paint removers raying
1.3 Details of the supp Manufacturer/Supplie MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 6944 Fax: +31 (0)561 6944 e-mail: msds@nl.motip	20 11
-	btainable from: Department Product Safety
1.4 Emergency telepho	
+31 (0)561-694400 (09	9:00h - 17:00h)
UK: NPIS National Po	isons Information Centre Tel: +44 0344 892 0111
SECTION 2: Haza	ards identification
0 0	ne substance or mixture ng to Regulation (EC) No 1272/2008
	ig to Regulation (EC) 110 1272/2000
GHS02 flam	e
\checkmark	
Aerosol 1 H222-H22	9 Extremely flammable aerosol. Pressurised container: May burst if heated.
GHS07	
Eye Irrit. 2 H319	Causes serious eye irritation.
STOT SE 3 H336	May cause drowsiness or dizziness.
SIUI SE S 11.3.0	
2.2 Label elements	• Regulation (EC) No 1272/2008

Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2020

Version number 72

Revision: 09.09.2020

Trade name: SIMPLY® SPRAYS MATT WHITE 500 ML

II.a. a. 1	(Contd. of page
Hazara p	ictograms
	\wedge
$\mathbf{\nabla}$	
GHS02	GHS07
011502	
Signal w	ord Danger
Hazard-a	letermining components of labelling:
acetone	
n-butyl a	cetate
butan-1-a	pl
Hazard s	tatements
Н222-Н2	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precautio	onary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smokin
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P410+P4	412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents / container in accordance with regional regulations.
Addition	al information:
EUH066	Repeated exposure may cause skin dryness or cracking.
Buildup d	of explosive mixtures possible without sufficient ventilation.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or
	mist.
2.3 Other	r hazards

• *PBT:* Not applicable.

· **vPvB:** Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2 Index number: 606-001-00-8	 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 	
Reg.nr.: 01-2119471330-49	U Eye Irru. 2, H519; S101 SE 5, H550	
CAS: 123-86-4	n-butyl acetate	10-<12.5%
EINECS: 204-658-1	🚸 Flam. Liq. 3, H226	
Index number: 607-025-00-1	🍈 STOT SE 3, H336	
Reg.nr.: 01-2119485493-29		
CAS: 74-98-6	propane	10-<12.5%
EINECS: 200-827-9	🚯 Flam. Gas 1A, H220	
Index number: 601-003-00-5	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119486944-21		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	5-<10%
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226	
Index number: 607-195-00-7		
Reg.nr.: 01-2119475791-29		(Contd. on page 3

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2020

Version number 72

Revision: 09.09.2020

Trade name: SIMPLY® SPRAYS MATT WHITE 500 ML

		Contd. of page 2
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane Flam. Gas IA, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide	2.5-<5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	 butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335- H336 	2.5-<5%
CAS: 9004-70-0	cellulose nitrate Flam. Sol. 1, H228 the wording of the listed hazard phrases refer to section 16.	<2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

 \cdot 5.2 Special hazards arising from the substance or mixture

- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

Mount respiratory protective device.

- Wear protective equipment. Keep unprotected persons away.
- \cdot 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

GB

Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2020

Version number 72

Revision: 09.09.2020

(Contd. of page 3)

Trade name: SIMPLY® SPRAYS MATT WHITE 500 ML

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep container tightly sealed.

· Storage class: 2 B

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingre	dients with limit values that require monitoring at the workplace:	
67-64	I-1 acetone	
WEL	Short-term value: 3620 mg/m³, 1500 ppm	
	Long-term value: 1210 mg/m³, 500 ppm	
123-8	6-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm	
	Long-term value: 724 mg/m³, 150 ppm	
108-6	5-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm	
	Long-term value: 274 mg/m³, 50 ppm	
	Sk	
106-9	7-8 butane	
WEL	Short-term value: 1810 mg/m³, 750 ppm	
	Long-term value: 1450 mg/m³, 600 ppm	
	<i>Carc (if more than 0.1% of buta-1.3-diene)</i>	
71-36	5-3 butan-1-ol	
WEL	Short-term value: 154 mg/m³, 50 ppm	
	Sk	
· Addit	ional information: The lists valid during the making were used as basis.	
· 8.2 E	xposure controls	
· Perso	nal protective equipment:	
	ral protective and hygienic measures:	
	away from foodstuffs, beverages and feed.	
	diately remove all soiled and contaminated clothing	
	hands before breaks and at the end of work.	
	ot inhale gases / fumes / aerosols.	
	contact with the eyes and skin.	
Avoia	contact with the eyes.	(Contd. on page 5)
		GB

Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2020

Version number 72

Revision: 09.09.2020

(Contd. of page 4)

GB

Trade name: SIMPLY® SPRAYS MATT WHITE 500 ML

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

• Protection of hands:



Protective gloves

• Material of gloves Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

• Eye protection:



*

Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties General Information	
· Appearance:	
Form:	Aerosol
Colour:	White
· Odour:	Solvent-like
• Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Not applicable, as aerosol.
· Flash point:	Not applicable, as aerosol.
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	333 °C (631.4 °F)
· Decomposition temperature:	Not determined.
· Explosive properties:	Not determined.
· Explosion limits:	
Lower:	1.2 Vol %
	(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2020

Version number 72

Revision: 09.09.2020

Trade name: SIMPLY® SPRAYS MATT WHITE 500 ML

	(Contd. of page
Upper:	13 Vol %
· Vapour pressure at 20 °C (68 °F):	3500 hPa (2625.2 mm Hg)
• Density at 20 •C (68 •F):	0.8 g/cm ³ (6.7 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	87.8 %
Water:	0.3 %
VOC (EC)	
	722.5 g/l
· VOC-EU%	87.76 %
· Solids content:	8.2 %
• 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

*

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	D/LC50 values relevant for classification:	
67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50/4h	76 mg/l (rat)
123-86-4 n	123-86-4 n-butyl acetate	
Oral	LD50	10800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/m3 (rat)
108-65-62	108-65-6 2-methoxy-1-methylethyl acetate	
Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	>10000 mg/m3 (rat)
		(Contd. on page

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2020

Version number 72

Revision: 09.09.2020

Trade name: SIMPLY® SPRAYS MATT WHITE 500 ML

 (Contd. of pag 71-36-3 butan-1-ol		
Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50 / 4 h	17000 mg/m3 (rat)
		

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

 \cdot Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- \cdot CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- \cdot Germ cell mutagenicity Based on available data, the classification criteria are not met.
- \cdot Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

67-64-1 acetone

LC50/96h 8300 mg/l (fish)

EC50/96h 7200 mg/l (algae)

LC50 / 48 h 8450 mg/l (crustacean (water flea))

108-65-6 2-methoxy-1-methylethyl acetate

EC50/48 h >500 mg/l (daphnia magna)

LC50 / 96 h 100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle)

71-36-3 butan-1-ol

LC50/96 h 1376 mg/l (fish)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- \cdot Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

(Contd. on page 8)

Page 8/10

2

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2020

Version number 72

Revision: 09.09.2020

(Contd. of page 7)

Trade name: SIMPLY® SPRAYS MATT WHITE 500 ML

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

SECTION 14: Transport information · 14.1 UN-Number UN1950 · ADR, IMDG, IATA · 14.2 UN proper shipping name 1950 AEROSOLS · ADR · IMDG AEROSOLS $\cdot IATA$ AEROSOLS, flammable · 14.3 Transport hazard class(es) · ADR · Class 2 5F Gases. · Label 2.1 · IMDG, IATA · Class 2.1 · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA not regulated · 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): · EMS Number: F-D, S-U· Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. (Contd. on page 9)

- GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2020

Version number 72

Revision: 09.09.2020

Trade name: SIMPLY® SPRAYS MATT WHITE 500 ML

	(Contd. of page 8)
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
\cdot Limited quantities (LQ)	1L
· Excepted quantities $(\widetilde{E}Q)$	Code: E0
· · · · · · · · · · · · · · · · · · ·	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· National regulations:

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H228 Flammable solid.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

· Department issuing SDS: R&D legislation and regulatory advisor

(Contd. on page 10)

GB

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2020

Version number 72

Revision: 09.09.2020

Trade name: SIMPLY® SPRAYS MATT WHITE 500 ML

	(Contd. of page
Contact: msds@nl.motipdupli.com	
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (I	Regulations Concerning the
International Transport of Dangerous Goods by Rail)	
ICAO: International Civil Aviation Organisation	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement c	concerning the International
Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
SVHC: Substances of Very High Concern	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1A: Flammable gases – Category 1A	
Aerosol 1: Aerosols – Category 1	
Press. Gas (Comp.): Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Flam. Sol. 1: Flammable solids – Category 1	
Acute Tox. 4: Acute toxicity - oral – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Carc. 2: Carcinogenicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
* Data compared to the previous version altered.	