

Page 1/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2020 Version number 114 Revision: 17.12.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SIMPLY® SPRAYS ADHESIVE SPRAY 400 ML
- · Article number: SP027
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC1 Adhesives, sealants
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Glue/ Sising agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

*Tel:* +31 (0)561 694400 *Fax:* +31 (0)561 694411

e-mail: msds@nl.motipdupli.com

- · Further information obtainable from: Department Product Safety
- 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Printing date 09.11.2020 Version number 114 Revision: 17.12.2019

Trade name: SIMPLY® SPRAYS ADHESIVE SPRAY 400 ML

(Contd. of page 1)

#### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07 GHS09

#### · Signal word Danger

#### · Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

pentane

butanone

isopentane

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

*P501* Dispose of contents / container in accordance with regional regulations.

#### · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- $\cdot$  **PBT:** Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components:   |  |         |
|---|--|---------|
| EC number: 921-024-6<br>Reg.nr.: 01-2119475514-35   | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336 | 25-<50% |
| CAS: 115-10-6<br>EINECS: 204-065-8<br>Index number: 603-019-00-8<br>Reg.nr.: 01-2119472128-37 | dimethyl ether  Flam. Gas 1A, H220 Press. Gas (Comp.), H280  | 20-<25% |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Index number: 601-003-00-5<br>Reg.nr.: 01-2119486944-21  | propane  Flam. Gas 1A, H220 Press. Gas (Comp.), H280   | 5-<10%  |

(Contd. on page 3)

Printing date 09.11.2020 Version number 114 Revision: 17.12.2019

Trade name: SIMPLY® SPRAYS ADHESIVE SPRAY 400 ML

| CAS: 106-97-8   | butane  | ontd. of page 2<br>5-<10% |
|---|---|---------------------------|
| EINECS: 203-448-7<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119474691-32                  | 🏇 Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280  |                           |
| CAS: 75-28-5<br>EINECS: 200-857-2<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119485395-27  | isobutane<br>Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280   | 5-<10%                    |
| CAS: 109-66-0<br>EINECS: 203-692-4<br>Index number: 601-006-00-1<br>Reg.nr.: 01-2119459286-30 | pentane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336                                | 5-<10%                    |
| CAS: 78-93-3<br>EINECS: 201-159-0<br>Index number: 606-002-00-3<br>Reg.nr.: 01-2119457290-43  | butanone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336   | 2.5-<5%                   |
| CAS: 78-78-4<br>EINECS: 201-142-8<br>Index number: 601-006-00-1<br>Reg.nr.: 01-2119475602-38  | isopentane  Flam. Liq. 1, H224  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  TOTO SE 3, H336                         | <2.5%                     |
| CAS: 68610-51-5<br>Reg.nr.: 01-2119496062-39  | phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene  Repr. 2, H361d Aquatic Chronic 4, H413 | <1%                       |

# SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

· Additional information: For the wording of the listed hazard phrases refer to section 16.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

  During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Printing date 09.11.2020 Version number 114 Revision: 17.12.2019

Trade name: SIMPLY® SPRAYS ADHESIVE SPRAY 400 ML

(Contd. of page 3)

#### · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

| · Ingredients with | limit values t | hat require | monitoring | at the w | vorkplace: |
|--------------------|----------------|-------------|------------|----------|------------|
|--------------------|----------------|-------------|------------|----------|------------|

#### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

#### 106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

#### 109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

### 78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

#### 78-78-4 isopentane

WEL Long-term value: 1800 mg/m³, 600 ppm

· Ingredients with biological limit values:

### 78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

(Contd. on page 5)

Printing date 09.11.2020 Version number 114 Revision: 17.12.2019

Trade name: SIMPLY® SPRAYS ADHESIVE SPRAY 400 ML

(Contd. of page 4)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Protection of hands:



Protective gloves

### · Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye protection: Not required.

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Colour: Whitish
Odour: Solvent-like
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gas): Not applicable.

(Contd. on page 6)

Printing date 09.11.2020 Version number 114 Revision: 17.12.2019

Trade name: SIMPLY® SPRAYS ADHESIVE SPRAY 400 ML

|   | (Contd. of page                            |
|---|--|
| · Ignition temperature:                   | >200 °C (>392 °F)                          |
| · Decomposition temperature:              | Not determined.                            |
| · Explosive properties:                   | Not determined.                            |
| · Explosion limits:                       |  |
| Lower:                                    | 0.6 Vol %                                  |
| Upper:                                    | 26.2 Vol %                                 |
| · Vapour pressure at 20 °C (68 °F):       | 4000 hPa (3000.2 mm Hg)                    |
| · Density at 20 °C (68 °F):               | $0.7 \text{ g/cm}^3 (5.8 \text{ lbs/gal})$ |
| · Relative density                        | Not determined.                            |
| · Vapour density                          | Not determined.                            |
| Evaporation rate                          | Not applicable.                            |
| · Solubility in / Miscibility with        |  |
| water:                                    | Not miscible or difficult to mix.          |
| · Partition coefficient: n-octanol/water: | Not determined.                            |
| · Viscosity:                              |  |
| Dynamic:                                  | Not determined.                            |
| Kinematic:                                | Not determined.                            |
| · Solvent content:                        |  |
| Organic solvents:                         | 86.8 %                                     |
| VOC(EC)                                   |  |
|   | 586.1 g/l                                  |
| · VOC-EU%                                 | 86.80 %                                    |
| · Solids content:                         | 10.8 %                                     |
| 9.2 Other information                     | No further relevant information available. |

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| · <i>LD/LC50</i> 1 | values relev                    | ant for classification:                        |  |
|--------------------|---------------------------------|--|--|
| Hydrocarb          | ons, C6-C7                      | , n-alkanes, isoalkanes, cyclics, <5% n-hexane |  |
| Oral               | Oral   LD50   >5840 mg/kg (rat) |  |  |
| Dermal             | Dermal LD50 >2920 mg/kg (rab)   |  |  |
| Inhalative         | LC50/4h                         | >25.2 mg/l (rat)                               |  |
| 109-66-0 р         | 109-66-0 pentane                |  |  |
| Oral               | Oral LD50 >5000 mg/kg (rat)     |  |  |
| Inhalative         | LC50/4h                         | 25.3 mg/l (rat)                                |  |

(Contd. on page 7)

Printing date 09.11.2020 Version number 114 Revision: 17.12.2019

Trade name: SIMPLY® SPRAYS ADHESIVE SPRAY 400 ML

(Contd. of page 6)

| 78-93-3 bu | ıtanone  |                      | (Contai or | ĺ |
|------------|----------|----------------------|------------|---|
| Oral       | LD50     | >2193 mg/kg (rat)    |            |   |
| Dermal     | LD50     | >5000 mg/kg (rabbit) |            |   |
| Inhalative | LC50/4 h | 34 mg/m3 (rat)       |            |   |

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

· 12.1 Toxicity

|   | · 12.1 Toxicity   |  |  |  |  |
|---|---|--|--|--|--|
|   | · Aquatic toxicity:   |  |  |  |  |
| Ī | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane |  |  |  |  |
| Ī | EC50 / 48 h   3 mg/l (daphnia magna)                              |  |  |  |  |
|   | EC50 / 72 h   30-100 mg/l (algae)                                 |  |  |  |  |
|   | LC50/96 h 11.4 $mg/l$ (fish)                                      |  |  |  |  |
| Ī | 115-10-6 dimethyl ether   |  |  |  |  |
| Ī | EC50 / 96 h   155 mg/l (algae)                                    |  |  |  |  |
|   | LC50 / 48 h >4000 mg/l (daphnia magna)                            |  |  |  |  |
|   | LC50/96 h $>4000 mg/l (fish)$                                     |  |  |  |  |
| Ī | 109-66-0 pentane  |  |  |  |  |
| Ī | EC50 / 48 h   9.7 mg/l (daphnia magna)                            |  |  |  |  |
|   | EC50/96 h 4.26 mg/l (fish)  |  |  |  |  |
|   | LC50/96 h 4.26 mg/l (fish)  |  |  |  |  |
| Ī | 78-93-3 butanone  |  |  |  |  |
| Ī | LC50 / 48 h   308 mg/l (daphnia magna)                            |  |  |  |  |
|   | LC50 / 72 h   1972 mg/l (Pseudokirchneriella Subcapitata)         |  |  |  |  |
|   | LC50 / 96 h 2990 mg/l (fish)                                      |  |  |  |  |

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 8)

Printing date 09.11.2020 Version number 114 Revision: 17.12.2019

Trade name: SIMPLY® SPRAYS ADHESIVE SPRAY 400 ML

(Contd. of page 7)

- · vPvB: Not applicable.
- $\cdot \textbf{12.6 Other adverse effects} \ \textit{No further relevant information available}.$

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| · European           | · European waste catalogue  |  |  |
|----------------------|---|--|--|
| 20 01 13*   solvents |   |  |  |
| 15 01 04             | metallic packaging  |  |  |
|                      | metallic packaging containing a hazardous solid porous matrix (for example asbestos), including |  |  |
|                      | empty pressure containers   |  |  |

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

| · 14.1 UN-Number<br>· ADR, IMDG, IATA       | UN1950  |
|---|---|
| 14.2 UN proper shipping name<br>ADR<br>IMDG | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS<br>AEROSOLS (Naphtha (petroleum), hydrotreated light,<br>PENTANES), MARINE POLLUTANT |
| · IATA                                      | AEROSOLS, flammable   |
| · 14.3 Transport hazard class(es)           |   |
| ADR   |   |
| Class Label                                 | 2 5F Gases.<br>2.1  |
| · IMDG                                      | · · · · · · · · · · · · · · · · · · ·   |
|   |   |
| Class                                       | 2.1   |
| Label                                       | 2.1   |
| IATA  |   |
| · Class                                     | 2.1   |
| Label                                       | 2.1   |

— GE

(Contd. on page 9)

Printing date 09.11.2020 Version number 114 Revision: 17.12.2019

Trade name: SIMPLY® SPRAYS ADHESIVE SPRAY 400 ML

|  | (Contd. of page  |
|--|--|
| 14.4 Packing group<br>ADR, IMDG, IATA        | not regulated  |
| 14.5 Environmental hazards:                  |  |
| Marine pollutant:                            | Symbol (fish and tree)                                     |
| Special marking (ADR):                       | Symbol (fish and tree)                                     |
| 14.6 Special precautions for user            | Warning: Gases.  |
| Hazard identification number (Kemler code):  |  |
| EMS Number:                                  | F- $D$ , $S$ - $U$   |
| Stowage Code                                 | SW1 Protected from sources of heat.                        |
|  | SW22 For AEROSOLS with a maximum capacity of 1 litro       |
|  | Category A. For AEROSOLS with a capacity above 1 litro     |
|  | Category B. For WASTE AEROSOLS: Category C, Clear          |
|  | of living quarters.  |
| Segregation Code                             | SG69 For AEROSOLS with a maximum capacity of 1 litre       |
|  | Segregation as for class 9. Stow "separated from" class 1  |
|  | except for division 1.4.                                   |
|  | For AEROSOLS with a capacity above 1 litre:                |
|  | Segregation as for the appropriate subdivision of class 2. |
|  | For WASTE AEROSOLS:  |
|  | Segregation as for the appropriate subdivision of class 2. |
| 14.7 Transport in bulk according to Annex II | of   |
| Marpol and the IBC Code                      | Not applicable.  |
| Transport/Additional information:            |  |
| ADR  |  |
| Limited quantities (LQ)                      | 1L   |
| Excepted quantities (EQ)                     | Code: E0   |
|  | Not permitted as Excepted Quantity                         |
|  | Code: E0   |
|  | Not permitted as Excepted Quantity                         |
| Transport category                           | 2  |
| Tunnel restriction code                      | D  |
| IMDG   |  |
| Limited quantities (LQ)                      | IL   |
| Excepted quantities (EQ)                     | Code: E0   |
| _ <del>_</del>                               | Not permitted as Excepted Quantity                         |
|  | Code: E0   |
|  | Not permitted as Excepted Quantity                         |
| UN "Model Regulation":                       | UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY                     |
|  |  |

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- $\cdot \textit{Named dangerous substances ANNEX I None of the ingredients is listed.}$
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)

Printing date 09.11.2020 Version number 114 Revision: 17.12.2019

Trade name: SIMPLY® SPRAYS ADHESIVE SPRAY 400 ML

(Contd. of page 9)

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: msds@nl.motipdupli.com
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 1: Flammable liquids – Category 1

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

· \* Data compared to the previous version altered.

GB